



TabLift™

BEACON BCDL Series Small Scissor Lift



Compact Double, Electrohydraulic 500 to 2,000 lb. Capacity For Surface or Pit Installation

BCDL -15-36-18036

Model Number Format

BCDL-15-36-18036

Series "BCDL" Compact Lift Table

Capacity 15 = 1,500 lbs.

Vertical Travel 36 = 36 inches

Platform Size 18036 = 18"W x 36"L

Description

BEACON BCDL Series Compact Double Scissor Lifts are high-speed electrohydraulic scissor lifts with capacities of 500 to 2,000 lbs., travel distance to 36 in. with platform size of 18 x 36 to 30 x 60 in.

All BEACON Lift Tables are designed and constructed for heavy-duty applications under the toughest working conditions, offering years of trouble-free operation.

Standard Features

- Internally-mounted ¾HP, 115V, 1PH, 60Hz intermittent duty TENV super torque motor
- 115V operating control voltage
- NEMA-4X constant-pressure (water-tight, dust-tight and corrosion-resistant) "UP-DOWN" push-button box with 8 ft. straight cord
- 10 ft. power cord (connector plug not included)
- Hard, chrome-plated, polished shafting, hydraulic cylinder piston rods and axles
- Surfaces degreased, oxide primed and finished with two coats of enamel
- Smooth steel tops and straight safety toeguards

- Lifetime self-lubricating, anti-friction bearings at all pivot points
- Internal high-pressure gear pump with check valve, relief valve, pressure-compensated flow control valve, solenoid valve, suction and return filters
- Includes hydraulic oil

Limited Warranty Policy

Refer to Warranty Form Number WF-0901 for specific details.

Specifications are subject to change without notice.

BCDL Series Scissor Lifts are one of a group of BEACON Lift Tables and other materials handling products.

Selector Table for BCDL Series. Capacities 500 to 2,000 lbs.

Travel	Model	Capacity (pounds)	Edge Load* Maximum Static	Platform Sizes (inches)		Base Frame (inches)	Height (Inches)		Up Speeds (seconds)	Motor Std. HP**	Cylinders (qty.)	Ship* Weight (pounds)
				Standard	Maximum		Lowered	Raised				
36"	BCDL-05-36	500	250	18 x 36	30 x 60	18 x 36	7	43	13	¾	1	250
	BCDL-10-36	1,000	500	18 x 36	30 x 60	18 x 36	7	43	13	¾	2	295
	BCDL-15-36	1,500	750	18 x 36	30 x 60	18 x 36	7	43	26	¾	2	320
	BCDL-20-36	2,000	1,000	18 x 36	30 x 60	18 x 36	7	43	26	¾	3	340

*Standard platforms only. **See options. Oversized platforms, beveled toeguards, roller shades, accordion skirting and electrical tape switches will affect overall size. Power requirements depend upon frequency and type of operation and require specific selection. See page 21 for options and accessories. Portability: HLT-PORT-1 (2) retractable poly wheels and (2) wheel dolly jack.