

HYDRAULIC POST TABLES



Foot operated hydraulic lift tables for heavy duty industrial shop use. Applications include; lifting dies and castings, moving machine parts, positioning welder's work, leveling pump presses, material handling and ergonomic work positioning.

Two-speed manual hydraulic foot pump for maximum operator convenience (on 4 post units). Foot pump includes down speed control valve.

The two and four post models include an ergonomic push handle and four casters, two rigid and two swivel with caster lock, attached with quick-change caster pads. The single post models have polyurethane casters, four swivel with caster lock. Optional low-profile and shorty pump design available.



SINGLE POST

STANDARD FEATURES

- Two-Speed Foot Pump (4 post)
- Ergonomic Push Handle (2 & 4 post)
- Phenolic Casters (2 & 4 post)



DC POWERED POST TABLE

Power lift models feature a DC electric motor to raise and lower the platform with the push of a button. Includes a 12V DC battery. Optional on-board charger and indicator available.



DIE TABLE



TWO POST

MODEL NUMBER	PLATFORM SIZE (WIDTH x LENGTH)	RAISED HEIGHT	LOWERED HEIGHT	CAPACITY (POUNDS)	NUMBER OF POSTS	OPERATION	WEIGHT (POUNDS)
BHT-02-1616	16" x 16"	49"	31"	200	1	FOOT PUMP	75
BHT-03-1618	16" x 18"	49"	31"	300	1	FOOT PUMP	125
BHT-05-1818	18" x 18"	54"	36"	500	2	FOOT PUMP	125
BHT-10-2036	20" x 36"	54"	36"	1,000	2	FOOT PUMP	300
BHT-20-2436	24" x 36"	54"	36"	2,000	4	FOOT PUMP	375
BHT-20-3036	30" x 36"	54"	36"	2,000	4	FOOT PUMP	390
BHT-20-3042	30" x 42"	54"	36"	2,000	4	FOOT PUMP	420
BHT-30-2436	24" x 36"	54"	36"	3,000	4	FOOT PUMP	380
BHT-30-3036	30" x 36"	54"	36"	3,000	4	FOOT PUMP	395
BHT-30-3042	30" x 42"	54"	36"	3,000	4	FOOT PUMP	425
BHT-60-2436	24" x 36"	54"	36"	6,000	4	FOOT PUMP	525
BHT-60-3248	32" x 48"	54"	36"	6,000	4	FOOT PUMP	540
BHT-20-2436-DC	24" x 36"	54"	36"	2,000	4	DC BATTERY	425
BHT-20-3036-DC	30" x 36"	54"	36"	2,000	4	DC BATTERY	445
BDIE-2430	24" x 30"	44"	29"	2,000	2	FOOT PUMP	280

MECHANICAL POST TABLES

HIGH OR LO-PROFILE DESIGN AVAILABLE



DC POWERED



Adjustable-height portable table is well suited for a wide variety of material handling applications. Mechanical crank mechanism provides positive height adjustment without downward drift. Two speed gear mechanism moves loads at 1/8" per crank rotation and light loads at 3/8" per crank rotation. 5" x 2" two rigid/two swivel polyurethane casters and floor lock standard.

Power lift option includes DC motor to automatically lift and lower platform, complete with battery and hand held control. Optional on board charger and battery indicator available.

MODEL NUMBER	PLATFORM SIZE (WIDTH x LENGTH)	RAISED HEIGHT	LOWERED HEIGHT	CAPACITY (POUNDS)	PROFILE	OPERATION	WEIGHT (POUNDS)
BMT-2436-LP	24" x 36"	42"	24"	2,000	LO-PROFILE	MECHANICAL	350
BMT-2442-LP	24" x 42"	42"	24"	2,000	LO-PROFILE	MECHANICAL	380
BMT-3042-LP	30" x 42"	42"	24"	2,000	LO-PROFILE	MECHANICAL	430
BMT-3048-LP	30" x 48"	42"	24"	2,000	LO-PROFILE	MECHANICAL	470
BMT-2436-HP	24" x 36"	46"	28"	2,000	HIGH-PROFILE	MECHANICAL	370
BMT-2442-HP	24" x 42"	46"	28"	2,000	HIGH-PROFILE	MECHANICAL	400
BMT-3042-HP	30" x 42"	46"	28"	2,000	HIGH-PROFILE	MECHANICAL	450
BMT-3048-HP	30" x 48"	46"	28"	2,000	HIGH-PROFILE	MECHANICAL	490
BMT-2436-LP-DC	24" x 36"	42"	24"	2,000	LO-PROFILE	DC POWERED	430

LONG DECK CART

The Long-Deck Cart is perfect for sheet and strip handling, ergonomic load positioning and handling long awkward material loads. The hydraulic foot pump delivers a service range of 31" lowered to 48" raised. Structural steel base helps to distribute the load evenly.

Unit comes standard with 2 swivel and 2 rigid 5" x 2" polyurethane casters and dual floor locks. Optional AC, DC and Air/Oil power available.



MODEL NUMBER	PLATFORM SIZE (WIDTH x LENGTH)	RAISED HEIGHT	LOWERED HEIGHT	CAPACITY (POUNDS)	WEIGHT (POUNDS)
BLDLT-3060	30" x 60"	48"	31"	2,000	450
BLDLT-3072	30" x 72"	48"	31"	2,000	485
BLDLT-3096	30" x 96"	48"	31"	2,000	525
BLDLT-30120	30" x 120"	48"	31"	2,000	580

Beacon Industries, Inc.

12300 Old Tesson Rd.
 St. Louis, MO 63128-2247 USA
 Phone: (314) 487-7600 Fax: (314) 487-0100
www.beaontechnology.com
 E-Mail: sales@beaontechnology.com