

INCREASE PRODUCTIVITY WITH

Specialty Strapping Machines



Model *BDBA-130*

Semi-Automatic Probe Pallet Strapper

- User Friendly
- 40" Foldable Arm
- Tension up to 175 lbs.
- Uses 3/8" or 1/2" Strapping

Eliminate hand strapping and speed up the process of pallet strapping with this Semi-Automatic Pallet Strapper. Unit automatically feeds the desired polypropylene strap through the pallet, tightens and seals the strap around the pallet.



DIMENSIONAL DRAWING

SPECIFICATIONS

Power Supply ... 110V, 1 Ph

Tension 175 lbs.

Coil Width (min) 7"

Coil Width (max) 9"

Weight 350 lbs.

OPERATION


- 1.) Unfold Chute/Leg
- 2.) Push Chute/Leg into Pallet
- 3.) Feed Polypropylene Strap
- 4.) Insert Tip of Strap into Strapway
- 5.) Adjust Tension, Pulling Automatically into Heat Seal.
- 6.) Strip is then Cut Off to Feed the Strap Out
- 7.) One Cycle Automatically Complete
- 8.) Remove Machine & Insert into Next Pallet

Series *BST*


Polypropylene Strapping

- Resists Splitting
- Core Size is 9" x 8"
- Smooth & Uniform
- Absorbs Shock Loading

MODEL	COLOR	STRAPPING WIDTH	FEET PER ROLL
BST-38-9X8-YL	YELLOW	3/8"	13,120
BST-38-9X8-WH	WHITE	3/8"	13,120
BST-38-9X8-NA	NATURAL CLEAR	3/8"	13,120
BST-12-9X8-YL	YELLOW	1/2"	9,840
BST-12-9X8-WH	WHITE	1/2"	9,840
BST-12-9X8-NA	NATURAL CLEAR	1/2"	9,840
BST-58-9X8-YL	YELLOW	5/8"	8,200
BST-58-9X8-WH	WHITE	5/8"	8,200
BST-58-9X8-NA	NATURAL CLEAR	5/8"	8,200



Yellow



White



Natural Clear

