

**INCREASE PRODUCTIVITY WITH**

# Specialty Strapping Machines



Model *BDBA-130*

## Semi-Automatic Probe Pallet Strapper

- User Friendly
- Tension up to 175 lbs.
- 40" Foldable Arm
- Uses 3/8" or 1/2" Strapping

Eliminate hand strapping and speed up the process of pallet strapping with this Semi-Automatic Pallet Strapper. Unit automatically feeds the desired polypropylene strap through the pallet, tightens and seals the strap around the pallet.



DIMENSIONAL DRAWING

**SPECIFICATIONS**

Power Supply ... 110V, 1 Ph

Tension ..... 175 lbs.

Coil Width (min) ..... 7"

Coil Width (max) ..... 9"

Weight ..... 350 lbs.

### OPERATION


- 1.) Unfold Chute/Leg
- 2.) Push Chute/Leg into Pallet
- 3.) Feed Polypropylene Strap
- 4.) Insert Tip of Strap into Strapway
- 5.) Adjust Tension, Pulling Automatically into Heat Seal.
- 6.) Strip is then Cut Off to Feed the Strap Out
- 7.) One Cycle Automatically Complete
- 8.) Remove Machine & Insert into Next Pallet

### Series *BST*


#### Polypropylene Strapping

- Resists Splitting
- Smooth & Uniform
- Core Size is 9" x 8"
- Absorbs Shock Loading

MODEL	COLOR	STRAPPING WIDTH	FEET PER ROLL
BST-38-9X8-YL	YELLOW	3/8"	13,120
BST-38-9X8-WH	WHITE	3/8"	13,120
BST-38-9X8-NA	NATURAL CLEAR	3/8"	13,120
BST-12-9X8-YL	YELLOW	1/2"	9,840
BST-12-9X8-WH	WHITE	1/2"	9,840
BST-12-9X8-NA	NATURAL CLEAR	1/2"	9,840
BST-58-9X8-YL	YELLOW	5/8"	8,200
BST-58-9X8-WH	WHITE	5/8"	8,200
BST-58-9X8-NA	NATURAL CLEAR	5/8"	8,200



**Yellow**



**White**



**Natural Clear**



## Model *BSTRAP-P2*

### Manual Pallet Probe

- Increase Productivity
- 40" Foldable Arm
- Economical, Fast, Easy
- Low Maintenance
- Equipment Tray (measures 19"W x 5-3/4"D)




The *Manual Cart Probe*, model **BSTRAP-P2**, is a quick and simple answer to a long time dilemma. To use simply transport unit to your loaded pallet, extend arm and run strapping to end clip. After strapping is secure roll cart into pallet along center stringer (A). The strapping/arm will then protrude out the other end allowing the operator to pull the strapping up and over pallet (B). Unit accepts polypropylene strapping.



## Model *BSTRAP-VH*

### Vertical/Horizontal Strapping Cart

- Easier to Load Strapping Coil from Skid
- Utilizes Steel Strapping
- Turn Handle to Adjust Height of Coil
- Turn Handle to go from Vertical to Horizontal



The *Vertical/Horizontal Strapping Cart*, model **BSTRAP-VH**, allows the operator to raise or lower strapping to pallet height. To use, simply engage outer detents (disengaging inner) and turn the removable handle until strap is in the horizontal position. Once in the horizontal position disengage the outer detents and engage the inner detents. The strap can now be raised and lowered from 28" down to 8" with the same turn handle. Each unit comes standard with 10" x 3" pneumatic wheels. The equipment tray measures 16"W x 5-1/2"D. Overall size is 27"W x 27"D x 40"H (to top of welded handle).

## Model *BS-2001*

### Semi-Automatic Strapping Machine

- Minimize Packaging Time
- Secure Contents
- Stainless Steel Surface
- Portable for Convenience
- Easy to Operate

This fully portable *Strapping Machine*, model **BS-2001**, dispenses, tightens and seals economical polypropylene strapping around packages or bundles greater than 3". Unit automatically tightens strap and joins the ends with a secure heat weld. The motor automatically switches off when not in use.

As the strap is inserted, the motor automatically restarts. Wall plug standard 115V/single-phase 15 amp. Overall size is 22-1/2"W x 35"L x 29"H.



*Mini Strapper, model BMSM-40, also available.*



User Friendly Control Panel

## Beacon Industries, Inc.

12300 Old Tesson Rd.  
St. Louis, MO 63128-2247 USA  
Phone: (314) 487-7600 Fax: (314) 487-0100  
[www.beacontechnology.com](http://www.beacontechnology.com)  
E-Mail: [sales@beacontechnology.com](mailto:sales@beacontechnology.com)