



- NOTES:
1. GUARD THICKNESS: 0.188 IN
 2. OVERALL HEIGHT:
 3. ALL HOLES: .5625 IN
 4. HOLES 2 IN FROM ENDS
 5. MID HOLES EVENLY SPACED
 6. FASTENERS AND HARDWARE NOT INCLUDED

NON RETURNABLE

This drawing and data contained herein, are the sole property of Beacon. This information is considered confidential and subject to return on demand. This drawing and contents cannot be reproduced or given to a 3rd party without the written consent of an authorized representative of Beacon. The sole intent of this drawing and data is to establish a written approval agreement between Beacon and customer for Beacon to proceed with manufacturing defined herein. Accepting this drawing in hardcopy, or any form of electronic communication, will be considered a binding agreement to these terms.

TOLERANCE SPECIFICATION (Unless Noted Otherwise)				DRAWN: Configurator		DATE: 11/13/2018		Beacon Industries, Inc. St. Louis, MO 63128 USA							
DIMENSION UNITS: (inches)				CHECKED:		DATE:									
<u>LINEAR:</u>				<u>PERPENDICULAR:</u>		SO #:		SHIP DATE:		TITLE					
0.X ± 0.06 (1/16")				┴ ± (1/16" / ft)		QTY:		CUSTOMER:							
0.XX ± 0.03 (1/32")						FINISH - PREPARATION: SSPC-SP6		FINISH - APPLICATION: Powder Coat							
0.XXX ± 0.010						FINISH - COLOR: Yellow		ESTIMATED WEIGHT:		SIZE C		DWG NO BPGWM436+3-YEL		REV	
<u>WELD:</u> +0.06/-0.00, —															
REMOVE BURRS															

APPROVAL BLOCK

☐ _____ APPROVED AS IS FOR MANUFACTURING.

☐ _____ APPROVED AS IS FOR MANUFACTURING WITH REVISIONS NOTED.

☐ _____ REVISE AS NOTED AND RESUBMIT.

INITIAL

NOTE: MANUFACTURING WILL NOT COMMENCE UNTIL THE SIGNED APPROVAL DRAWING IS RECEIVED BY BEACON INDUSTRIES.

SIGNATURE

DATE

000000