

BearClaw® FIXED & ADJUSTABLE STEEL GANTRY CRANES

Beacon Industries, Inc. - 12300 Old Tesson Rd.
St. Louis, MO 63128-2247 USA - Phone: (314) 487-7600
Fax: (314) 487-0100 - E-Mail: sales@beacontechnology.com
beacontechnology.com

series BAHS

LOADING/UNLOADING AREAS

LIFTING & MOVING BULKY OBJECTS

Industrial Steel Gantry Cranes are designed for transporting and positioning materials. Solid steel construction will provide for years of service. Choose from a variety of sizes. Large 8" diameter locking phenolic casters with roller bearings will facilitate easy mobility from one area to another. More economical and flexible than permanent cranes. Features quick setup design. Order optional Lever Ratchet for easy one-person height adjustment (not for fixed height models). Height is adjustable in 6" increments on adjustable-height models. Blue finish.

** NOTE: All products should be inspected frequently to insure safe operation. Final testing and inspection is left to end user after final assembly has been completed. For further details see ASME B30.17.*



Optional Festoon Kit,
BAHS-FES-KIT



Optional Total Locking Casters,
BAHS-TLC (2,000 & 4,000 lb.), BAHS-6-TLC (6,000 lb.)

PORTABLE GANTRY CRANE

MODEL NUMBER	UNDER I-BEAM TO GROUND	*BEAM LENGTH	BEAM HEIGHT	FLANGE WIDTH	BASE WIDTH	CAPACITY (POUNDS)
BFHS-500	5'9"	8'	4"	2.66"	48"	500
BFHS-2-10	10'	10'	5"	3"	60"	2000
BFHS-2-15	10'	15'	6"	3.33"	60"	2000
BFHS-2-20	10'	20'	8"	4"	60"	2000
BFHS-4-10	10'	10'	8"	4"	60"	4000
BFHS-4-15	10'	15'	8"	4"	60"	4000
BFHS-4-20	10'	20'	10"	4.66"	60"	4000

*Deduct 12" for distance between upright.

A FRAME HOIST

MODEL NUMBER	UNDER I-BEAM RANGE	*BEAM LENGTH	BEAM HEIGHT	FLANGE WIDTH	BASE WIDTH	CAPACITY (POUNDS)
BAHS-2-10-12	9' to 12'	10'	5"	3	78"	2,000
BAHS-2-10-14	11' to 14'	10'	5"	3	90"	2,000
BAHS-2-15-12	9' to 12'	15'	6"	3.33	78"	2,000
BAHS-2-15-14	11' to 14'	15'	6"	3.33	90"	2,000
BAHS-2-20-12	9' to 12'	20'	8"	4	78"	2,000
BAHS-2-20-14	11' to 14'	20'	8"	4	90"	2,000
BAHS-4-10-12	9' to 12'	10'	8"	4	78"	4,000
BAHS-4-10-14	11' to 14'	10'	8"	4	90"	4,000
BAHS-4-15-12	9' to 12'	15'	8"	4	78"	4,000
BAHS-4-15-14	11' to 14'	15'	8"	4	90"	4,000
BAHS-4-20-12	9' to 12'	20'	10"	4.66	78"	4,000
BAHS-4-20-14	11' to 14'	20'	10"	4.66	90"	4,000
BAHS-6-10-12	9' to 12'	10'	8"	4	78"	6,000
BAHS-6-10-14	11' to 14'	10'	8"	4	90"	6,000
BAHS-6-15-12	9' to 12'	15'	10"	4.66	78"	6,000
BAHS-6-15-14	11' to 14'	15'	10"	4.66	90"	6,000
BAHS-6-20-12	9' to 12'	20'	10"	4.66	78"	6,000
BAHS-6-20-14	11' to 14'	20'	10"	4.66	90"	6,000
BAHS-8-10-12	9' to 12'	10'	10"	5	78"	8,000
BAHS-8-10-14	11' to 14'	10'	10"	5	90"	8,000
BAHS-8-15-12	9' to 12'	15'	10"	5	78"	8,000
BAHS-8-15-14	11' to 14'	15'	10"	5	90"	8,000
BAHS-8-20-12	9' to 12'	20'	12"	5	78"	8,000
BAHS-8-20-14	11' to 14'	20'	12"	5	90"	8,000

* Deduct 12" for distance between upright.

• Usable "Trolley Travel" length between the uprights is the overall length minus 30"