Pallet Pullers



Model	Jaw Height	Jaw Opening	Chain Length
BPAL-12	2³/₄" (7cm)	51/2" (14 cm)	30" (76 cm)
BPAL-14	1 ¹ /2" (4 cm)	3 ¹ /2" (9 cm)	6" (15 cm)
BPAL-21	2 ³ /4" (4 cm)	41/2" (11cm)	4 ¹ /2" (11cm)
BPAL-LP	1 ³ /4" (4.5 cm)	4 ¹ /2" (11cm)	30" (76 cm)

RATING

Pallet Pullers are rated to pull a 5000 lbs. skid across a smooth truck floor. DO NOT USE FOR LIFTING

 Cammed closing Double scissor acaction. tion. Safety handle for Rugged steel ease in postioning. construction. • Utilize with wood, · Concave multiplastic, and metal dimensional teeth. pallets. • For Stringers up to • Weight 14 lbs. 4¹/₂" (11cm) Wide. • Weight 21 lbs. **MODEL BPAL-21 MODEL BPAL-14** • Single scissor action. • Fits lower height pallets. • Our most popular Same Solid model. construction as • Convex teeth. Overall length 19 PAL-21. Lowest jaw height (closed). • Overall width 14" of scissor action pullers. (1.75 inches) (closed). • Weight 20 lbs. • Weight 12 lbs. **MODEL BPAL-12 MODEL BPAL-LP**

Model BPPC-20 and Model BPPC-40 20' (6 m) and 40' (12 m) galvanized proof coil chains complete with grab hooks at each end



Attach Pallet Puller to Fork Truck With a Proof Coil Chain

The Convenient And Low Cost Way To Move Pallets To The Rear Of Trailers



PRY LEVER BAR



STEEL PRY LEVER BAR

- 5,000 lbs. capacity
- 5, 6 and 7 foot handles
- All welded steel construction
- 5" x 2" polyurethane casters
- Flush Plate with reversed beveled edge
- Weight 35 lbs.



The above has all the standard features of the steel pry lever bar, with the addition of a revolutionary locking system. Simple to operate ---- Push handle down, depress pedal and the bar keeps the crate up. To disengage, push handle down and lift locking pedal with hand or foot.

WOOD PRY LEVER BAR

- 4,250 lbs. capacity
- 5, 6 and 7 foot handles
- Flush nose plate with beveled edge
- 5" x 2" polyurethane casters
- Weight 34 lbs.



Beacon Industries, Inc. 12300 Old Tesson Rd. St. Louis, MO 63128-2247 USA Phone: (314) 487-7600 Fax: (314) 487-0100 www.beacontechnology.com E-Mail: sales@beacontechnology.com