

YARD RAMPS



12300 Old Tesson Rd.
 St. Louis, MO 63128-2247 USA
 Phone: (314) 487-7600
 Fax: (314) 487-0100
 beacontechology.com
 E-Mail: sales@beacontechology.com

Ground Level Trailer Access


Reduction in Material Handling Costs

Expeditious Loading & Unloading

Dock Mobility

SAFETY FEATURES

- Positive Steel Traction Grating
- Safety Locking Chains
- 9" Steel Wheels
- 4" High Safety Curbs
- Manual Hand Crank Systems for Height Adjustment
- Rubber Bumpers
- 15" Overlap Lip
- YRD Series Hydraulic Edge-O-Dock



STEEL GRATING



SAFETY LOCKING CHAINS WITH 15" OVERLAP LIP

STANDARD FEATURES

- Capacities: 15,000 / 20,000 / 25,000 and 30,000 lbs.
- Lengths: 30 ft. straight ramp or 36 ft. (30 ft. ramp with 6 ft. level off)
- Widths: overall 73" with usable of 66" and 85" with usable of 78"
- 96" overall width available (call factory for details)
- Service Height Range 45" to 62"



MANUAL HAND CRANK & 9" STEEL WHEELS



TOW BAR LOOP



HAND RAILS



FORK LIFT PICK-UP SLOTS

OPTIONS

- Pneumatic Tires and Hand Pump Hydraulic (not available on **YRD** models)
- Pneumatic Tires and DC Hydraulic Lift (not available on **YRD** models)
- Mechanical Edge of Dock in lieu of Hydraulic (on **YRD** models, 15,000 and 20,000 lbs. capacity)
- Fork Lift Pick-up Slots
- Tow Bar Loop
- Tow Bar Hitch
- Hand Rails (42" high with 21" mid-rails)



HYDRAULIC HAND PUMP



27" PNEUMATIC TIRES