

Compression Dock Seal – B100 Series Fits Overhead Door Sizes: 8' wide x 8' tall & 8' wide x 9' tall. Dock Door Seal with Fixed Side Pads and Fixed Head Pad.

Foam-filled side pads and fixed head pad provides the most effective seal and the most economical solution for any Dock Door Size ranging from 8' wide x 9' tall opening.

Features

- Virgin polyurethane foam cut in-house to your specifications.
- Pressure treated lumber.
- 3" wide yellow guide-stripe on full length of side pads allows easy spotting by vehicle driver.
- Breather vent holes on side pads and head pad allow air and moisture to be released.
- 3" inside draft flap provides better bottom seal between bumpers.
- Durable fabrics in a wide range of weights, styles and colors.
- Bottom of side pads are tapered to prevent excessive wear.
- Hardware is galvanized or zinc-coated.

Options

- Extra-high Head Pads: 18" or 24" are available for docks lower than standard height or for docks servicing a variety of trailer heights.
- Drop-curtain: 12" can be added to head pad to accommodate 9' high door openings or for docks servicing a variety of trailers.
- Wear Pleats: Extra fabric flaps can be sewn to the front of the side pads and head pad to provide added durability and to extend the life of the seal. Recommended for heavy dock traffic.
- Tapered Side Pads: For sloped driveway applications at no additional cost.
- Wear Face: Extra layer of fabric sewn directly onto heavy wear areas – front of side pads, inside the wedge area or across the head pad face. Recommended for heavy dock traffic.
- Build-outs: Wooden frames are constructed, then covered with fabric and designed to extend the seal beyond an extra deep dock or platform situation.
- Galvanized steel back board.
- 23 oz. and 40 oz. fire-resistant fabric.



FABRIC SELECTION OVERVIEW

Fabric	Color Selection	Abrasion Strength	Tensile Strength	Tear Strength	Cold Resistance
<input type="checkbox"/> 50oz. Hybrid*	<input type="checkbox"/> Black	10,000 cycles	1,450 x1,090 lbs/in	250 x250	-40°F
<input type="checkbox"/> 40oz. vinyl	<input type="checkbox"/> Black <input type="checkbox"/> Blue <input type="checkbox"/> Brown <input type="checkbox"/> Green	3,000cycles	700 x700 lbs/in	165 x160	-30°F
<input type="checkbox"/> 22oz. vinyl	<input type="checkbox"/> Black <input type="checkbox"/> Blue <input type="checkbox"/> Brown <input type="checkbox"/> Green	1,000cycles	135 x145 lbs/in	140 x140	-30°F
<input type="checkbox"/> 40oz. hypalon	<input type="checkbox"/> Black 3,200cycles		520 x475 lbs/in	70x70	-50°F
Test Method	n/a	FS-5306	FS-5100	FS-5134	FS-5874

* The 50 oz. material is a hybrid custom-designed fabric that offers superior durability, with physical properties that far exceed standard industry fabrics.